



E-Z-GO LIBERTY OVER THE TOP ENCLOSURE INSTALLATION INSTRUCTIONS

ENCLOSURE INSTALLATION

1. Lay the enclosure onto the roof of the golf car with the pocket towards the front of the golf car.
2. Pull the pocket of the enclosure slightly out past the front edge of the roof.
3. Slide the enclosure towards the back of the car, allowing the roof of the golf car to slip into the pocket of the enclosure.
4. Attach the elastic straps at the back of the enclosure around the rear struts.
5. Allow the doors and rear panel of the enclosure to fall down into place.
6. Completely unzip and remove the attachment portion (sleeves) from the front door of the enclosure.

SLEEVE INSTALLATION

1. Remove the windshield from the car.
2. Remove the bolt that holds the support arm to the windshield frame.
3. Unzip the sleeves from the enclosure.
4. Wrap the sleeve around the windshield frame so that the cutout for the windshield retention clip is in the proper position.
5. Engage the smaller zipper so that it wraps snugly around the windshield frame (struts). The small sleeve zipper should be on the backside of the windshield frame.
6. Attach the sleeve to the enclosure, adjusting the height of the sleeve as necessary for even alignment with the enclosure zipper.
7. There should be a small X cut in the sleeve to allow for the replacement of the support arm bolt to the windshield. If there is no X, simply cut a small X where you feel the bolt hole.
8. Re attach the windshield by carefully snapping the windshield extrusion around the sleeve and frame and replace the support arm bolt.